

MOTOR TYPE	POWER		U _N	n _N	I _N	I _A	η - EFFICIENCY			Cosφ - POWER FACTOR			τ _N	τ _N	AXIAL LOAD
							η - VERİMLİLİK			Cosφ - GÜÇ FAKTÖRÜ					
	GÜÇ						at % load / % yükte			at % load / % yükte					EKSENEL YÜK
MOTOR TİPİ	HP	KW	V	rpm	A	A	50	75	100	50	75	100	Nm	Nm	kN
KM6-5.5	5.5	4	380	2869	9.2	35.7	76	77	76	0.72	0.82	0.86	13.1	15.5	20
			400	2887	8.8	34.1	76	78	78	0.69	0.79	0.85	13.0	17.2	
			415	2899	8.5	33.0	76	79	79	0.66	0.77	0.83	12.9	18.7	
KM6-7.5	7.5	5.5	380	2857	12.5	48.5	78	79	77	0.72	0.82	0.86	18.1	15.4	20
			400	2877	11.9	46.2	78	80	79	0.68	0.79	0.85	18.0	17.2	
			415	2890	11.5	44.6	78	80	80	0.66	0.77	0.83	17.8	18.5	
KM6-10	10	7.5	380	2876	16.9	65.6	78	80	79	0.68	0.79	0.85	24.5	18.9	20
			400	2893	16.2	62.9	78	81	80	0.65	0.77	0.83	24.3	21.1	
			415	2903	15.8	61.3	78	81	81	0.63	0.74	0.81	24.2	23.0	
KM6-12.5	12.5	9.3	380	2872	20.7	80.3	80	81	80	0.69	0.79	0.85	30.5	25.5	20
			400	2888	19.8	76.8	80	82	81	0.65	0.77	0.83	30.4	28.5	
			415	2899	19.3	74.9	80	82	82	0.63	0.74	0.82	30.2	30.7	
KM6-15	15	11	380	2879	24.6	95.4	80	82	81	0.66	0.77	0.84	36.0	30.9	20
			400	2894	23.7	92.0	80	82	82	0.63	0.75	0.82	35.8	34.8	
			415	2903	23.1	89.6	80	82	83	0.6	0.72	0.8	35.5	37.4	
KM6-17.5	17.5	13	380	2882	29.1	112.9	80	82	82	0.64	0.76	0.83	42.5	44.4	20
			400	2897	28.1	109.0	80	83	83	0.61	0.73	0.8	42.2	49.6	
			415	2906	27.6	107.1	80	83	83	0.58	0.71	0.79	42.0	53.8	
KM6-20	20	15	380	2873	31.8	123.4	83	84	83	0.7	0.81	0.86	49.0	53.2	20
			400	2889	30.5	118.3	83	85	84	0.67	0.78	0.84	48.8	59.7	
			415	2899	29.7	115.2	83	85	85	0.64	0.76	0.83	48.6	64.6	
KM6-25	25	18.5	380	2863	39.6	153.6	83	84	83	0.69	0.8	0.85	60.7	74.0	20
			400	2880	38	147.4	83	85	84	0.65	0.77	0.84	60.4	83.2	
			415	2891	37.1	143.9	83	85	85	0.63	0.75	0.82	60.1	89.9	
KM6-30	30	22	380	2868	46.5	180.4	84	85	84	0.68	0.79	0.85	72.2	90.7	20
			400	2884	44.8	173.8	84	86	85	0.65	0.76	0.83	72.0	101.5	
			415	2894	43.7	169.6	85	86	86	0.62	0.74	0.82	71.7	110.0	
KM6-35	35	26.5	380	2864	56.2	218.1	85	85	84	0.67	0.79	0.85	87.1	122.0	26.5
			400	2881	54.1	209.9	85	86	85	0.64	0.76	0.83	86.9	136.8	
			415	2891	52.9	205.3	85	86	86	0.62	0.74	0.81	86.6	148.4	
KM6-40	40	30	380	2838	61	236.7	86	86	85	0.75	0.84	0.88	99.3	135.7	26.5
			400	2858	58	225.0	87	87	86	0.72	0.82	0.87	99.0	152.0	
			415	2871	56.1	217.7	87	87	86	0.7	0.81	0.86	98.8	164.0	
KM6-50	50	37	380	2833	76.1	295.3	86	86	84	0.73	0.83	0.88	122.6	193.6	26.5
			400	2854	72.4	280.9	86	87	85	0.7	0.81	0.87	122.3	217.1	
			415	2867	70.2	272.4	87	87	86	0.68	0.79	0.85	122.0	235.4	
KM6-60	60	45	380	2805	97	376.4	85	84	83	0.66	0.79	0.87	148.4	234.4	26.5
			400	2830	92.8	360.1	85	85	84	0.61	0.73	0.84	148.1	262.9	
			415	2845	90.8	352.3	85	85	84	0.59	0.72	0.81	147.8	285.2	